



665 CAMEL



Elite *Specca*TM







635 BLACK OPAL

Specifications

Construction	5/64" Interlocking Level Loop
Fibre	Soln Dyed BCF Nylon/Strudon® Blend
Pile Weight	ca. 880g/m ² (26 oz/y ²)
Total Weight	ca. 1710g/m ² (50 oz/y ²)
Density	7200 FHA (9.1 kilotex/cm ²)
Pile height	ca. 4mm
Stitches	30.7/10cm (7.8/inch)
Backing System	ZipperLock® Dual Bonding
Pattern Repeat	0.7 x 1.0 cm

Performance

Stain Resistance	Stain Proof
Stain / Soil Protection	Scoured & Extracted™
Static Generation	Maximum 3.0 kV
Flammability	DOC FF 1-70 (USA)
Lightfastness	L5
Colour Fastness	Grey Scale 5

Warranties

10-year Carpet Wear Warranty
Lifetime Antishock Carpet Warranty
Stain Proof - No Exceptions™

Ideal for Heavy Commercial Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing.

Where seaming is necessary, a seam sealant **must** be used for all such installations.

Due to dyelot variations, actual material may vary slightly from the samples.

Chair pads are recommended to prevent premature wear of carpet.



Elegance & Comfort in Modern Living

Manufactured in Canada