

5843 Beach House



Lancelot™







5855 Twilight

Specifications

Construction Fibre Pile Weight Total Weight Pile height Stitch Rate

Density **Backing System** Standard Roll Size

Pattern Repeat

1/10" Textured Cut & Loop Pattern 100% BCF Ultrel:indelible™ Nylon ca. 1085g/m² (32 oz/y²) ca. 2010g/m² (60 oz/y²) ca. 3mm (cut), 6mm (loop)

48 per 10cm

11.4 Kilotex/cm² (5600 FHA) FullCircle™: 10% Recycled Content

3.66 x 40m

10 x 14 cm (4"x5 1/2")

Warranties

10-year Limited Commercial Carpet Wear Warranty Lifetime Stain Proof Warranty - No Exceptions^{TI} Lifetime "No delamination" Carpet Warranty Lifetime AccuPattern™ Warranty Lifetime Colorfast Carpet Warranty Lifetime Antishock Carpet Warranty

Ideal for Heavy Commercial Use

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing.

Where seaming is necessary, a seam sealant must be used for all such installations. Due to dyelot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

Performance

Flammability

Stain Resistance

Lightfastness

Canada: CGSB 4GP-129 CAN 4-S102.2

Radiant Panel Class 1 (ASTM E-648) 8.0 (AATCC 175-1993)

Soil Protection $\mathsf{PermaSeal}^\mathsf{TM}\,\mathsf{protected}$ Biofresh[™] present in backing laminate Maximum 3.0Kv Anti-Microbial Protection Static Generation

Change on Wet Cleaning Grey Scale 5













Stain Proof No Exceptions™

Sustainability Comprehensive Warranties BioFresh™ Anti-Microbial

AccuPattern™

CRI Green Label +Plus m



Elegance & Comfort in Modern Living

Manufactured in Canada