

## Product card Sport

### I. Description

**Sport** - a multi-layer heterogeneous covering with non-transparent coloured wear layer. Available in sheets. Protected with polyurethane PUR. Designed for sports facilities, e.g. multifunctional gymnasiums, sports halls, body building gyms and fitness clubs.

Rooms with Sport flooring can also be used for activities other than sports practice.

### II. Technical parameters

Parameters	Standard no	Requirements
Warranty period (years)	----	10
Surface protection	----	Polyurethane PUR
Declaration of Performance	PN-EN 14904	08-01-ZW
Reaction to fire	PN-EN 13501-1	B <sub>fl</sub> -s1
Hygiene attest	----	Pass
Total thickness	PN-EN ISO 24346	3,2 mm
Thickness of wear layer	PN-EN ISO 24349	1,10 mm
Weight	PN-EN ISO23997	5100 g/m <sup>2</sup>
Roll width	PN-EN ISO 24341	2 m
Roll length	PN-EN ISO 24341	9* m
Shock absorption	PN-EN 14808	58 %
Vertical deformation	PN-EN 14809	2,7 mm
Vertical ball behavior	PN-EN 12235	90 %
Slip resistance	PN-EN 13036-4	110
Wear resistance	PN-EN ISO 5470-1	193 mg
Specular reflectance	PN-EN ISO 2813	13 %
Resistance to indentation	PN-EN 1516	≤ 0,1 mm
Resistance to impact	PN-EN 1517	No damage
Resistance to a rolling load	PN-EN 1569	No damage
Dimensional stability after exposure to heat	PN-EN ISO 23999	≤ 0,4%
Curling after exposure to heat	PN-EN ISO 23999	≤ 8 mm
Light resistance	PN-ISO 105-B02	≥ 6
Chemical resistance	PN-EN ISO 26987	Resistant
Floor heating up to	----	do 27°C

\* Standard length. On the client's request, after prior consultation, the length may be up to 12 lm (rounded to the full meter).